


THE "CONVERTIBLE" DE CLOET PULL TYPE RAKE




Via A. Bucchi,2 - zona ind.le nord
06012 Citta' di Castello (Pg) - Italy
tel. +39 075 8521881
fax +39 075 8521439
e-mail: info@decloet.it
www.decloet.it

AGRICULTURE

The new "CONVERTIBLE" De Cloet pull type rake converts easily from a "V" configuration into a "V+2" configuration and vice versa without changes in the frame design. The unique innovations and new patented features include:

- Universal raking wheel arms eliminating the problem of right or left arms.
- Prismatic bar section for fine tuning ensures perfect adjustment to terrain.
- Hydraulic opening and closing of rear frame from tractor seat for windrow width adjustment from 4' 10" to 6' 2".
- The new "V+2" extension is optional and easy to add on at any time. Available with hydraulics or a mechanical version for transversal adjustments.
- The convertible pull type rakes are available with traditional right and left raking wheels or can be supplied with our new patented universal raking wheels with a robust 5mm. flange.



- 1 - Hydraulic or mechanical rear frame adjustment.
 - 2 - Add on "V+2" extension.
 - 3 - Universal rake wheel arm.
 - 4 - Prismatic bar section for fine tuning.
 - 5 - Transport bars.
- Optional double wheels on request.

MODEL	RVD-10	RVD-10V+2	RVD-12	RVD-12V+2	RVD-14	RVD-14V+2
WORKING WIDTH	24' - 6"	24' - 6"	27' - 8"	27' - 8"	31' - 8"	31' - 8"
TRANSPORT WIDTH	8' - 2"	8' - 2"	8' - 2"	8' - 2"	8' - 2"	8' - 2"
OVERALL LENGTH	26' - 3"	32' - 7"	28'	34' - 5"	31' - 2"	37' - 6"
WEIGHT LBS.	2914	3189	3256	3532	3598	3918
TIRE SIZE	205/70R15	205/70R15	205/70R15	205/70R15	205/70R15	205/70R15

Distributed by:

Dealer contact: